


This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

Applicant:	LED Linear GmbH	Manufacturer:	LED Linear GmbH
Address:	Dr.-Alfred-Herrhausen-Allee 20 47228 Duisburg	Address:	Dr. Alfred Herrhausen Allee 22 A-D + 20 A-D 47228 Duisburg
Country:	Germany	Country:	Germany
Party Authorized To Apply Mark:	Same as Manufacturer		
Report Issuing Office:	Intertek Deutschland GmbH, Kaufbeuren		
Control Number:	<u>4004471</u>	Authorized by:	 _____
			for L. Matthew Snyder, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.
545 East Algonquin Road, Arlington Heights, IL 60005
Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672

Standard(s):	Low Voltage Lighting Systems [UL 2108:2015 Ed.2+R:18Apr2023]
Product:	Luminaires [CSA C22.2#250.0:2021 Ed.5+U1;U2]
Brand Name:	LED LINEAR™ A Fagerhult Group Company

VarioLED may be followed by HYDRA, HYD, ECO, NEXUS, RGB, IQ W, IQW, IQ, IQ W Aton, IQ W Hydra, Aton Air, Xoominescent, Luminaris ECO, Linus, Linus+, LUMINARIS, PRO, EXL, IQW HYD, IQW NEX; may be followed by LD, HD, SLD, P12, P23; may be followed by 3 to 42; may be followed by L500, L1000, L1500, L2200; may be followed by B, G, R; may be followed by W; may be followed by 8, 9; may be followed by 20 to 50; may be followed by 0,05 to 5,040; may be followed by 50 to 5040; may be followed by m; followed by IP67.

VarioLED followed by HE, HC, HEC, IQ W HYD, IQW, RGB, R, G, B; may be followed by LD, HD, SLD; may be followed by 3 to 36; may be followed by W, TW; may be followed by 8, 9; may be followed by 18 to 99; may be followed by 1900 to 6000; may be followed by 82 to 4019; followed by DC, MO, OO, OT; followed by C00, C15, C30, C45, PCL, X; may be followed by X; may be followed by three characters; followed by IP67.

VarioLED FLEX may be followed by HYDRA, HYD, ECO, NEXUS, RGB, IQ W, IQW, IQ, IQ W Aton, IQ W Hydra, Aton Air, Xoominescent, Luminaris ECO, Linus, Linus+, LUMINARIS; followed by LD, HD, SLD, P12, P23; may be followed by 3 to 20; may be followed by L500, L1000, L1500, L2200; may be followed by B, G, R; may be followed by W; may be followed by 8, 9; may be followed by 20 to 50; may be followed by 0,05 to 10,019; may be followed by 50 to 10019; may be followed by m; followed by IP67.

Models:

VarioLED FLEX followed by HE, HC, HEC, ECO, RGB, IQW, R, G, B; may be followed by LD, HD, SLD; may be followed by 3 to 20; may be followed by W, TW; may be followed by 8, 9; may be followed by 18 to 99; may be followed by 1900 to 6000; followed by 50 to 10019; may be followed by DC, MO, OO, OT; may be followed by CLC, AT, X; followed by IP67.

HYDRALUX may be followed by HYDRA, HYD, ECO, NEXUS, RGB, IQ W; followed by LD, HD, SLD; followed by 3 to 20; may be followed by W; may be followed by 8, 9; may be followed by 20 to 50; may be followed by 0,165 to 5,040; may be followed by m; followed by IP67.

VarioLED Flex followed by VENUS, PHOBOS, SKYLLA; may be followed by IQ White, RGB, Red, Green, Blue, White, IQW, R, G, B; may be followed by LD, HD; may be followed by 3 to 42; may be followed by W; may be followed by 8, 9; may be followed by 20 to 50; may be followed by /; followed by 88,5 to 5040; may be followed by mm; may be followed by SV, TV; followed by IP67, IP68.

VENUS followed by TV, SV; may be followed by SW, IQW, RGB, COLOR; may be followed by HE, HC, HEC, R, B, G; followed by 4 to 20; may be followed by W, TW; may be followed by 8, 9; may be followed by 18 to 99; may be followed by 1900 to 6000; followed by 77 to 5040; followed by DC, MO, OO, OT; may be followed by X; may be followed by three characters; followed by IP67.

VarioLED Flex AMOR may be followed by LD, HD, B, R, G; may be followed by 3 to 20; may be followed by W; followed by 8, 9; followed by 20 to 50; followed by 79 to 5016; may be followed by mm; may be followed by SV; followed by IP67.

ADONIS may be followed by TC; followed by HYD, IQ W ATON, IQW ATON, IQ ATON, ATON IQ white, ECO, IQ W HYD, RGB, RGB 4S, IQ WHITE ATON, IQ WHITE HYDRA, HYDRA, NEX, RGBW, NEXUS, SOL, NEX IQW, NEX IQ W, NEX IQ WHITE, NEX IQWHITE, NEXUS IQ W, NEXUS IQW, NEXUS IQ WHITE, NEXUS IQWHITE, Linus, Linus+, LIN, LUMINARIS , LUM, LUMINARIS ECO, LUM ECO, IQW HYD, IQW NEX, IQ W NEX, H IQ, N IQ, S IQ, PRO, EXL, SW, IQW, ECO; may be followed by HE, HC; may be followed by LD, HD; may be followed by 3 to 42; may be followed by R,G,B,A; may be followed by P12 or P23; may be followed by L500, L1000, L1500, L2200; may be followed by W; may be followed by 8, 9; may be followed by 19 to 65; may be followed by 2030 or 2250; may be followed by 77 to 4014; may be followed by 0,077 to 4,014; may be followed by W, B or G; may be followed by 10 to 90; may be followed by E, AS or OL; may be followed by DC, MO, OO or OT; may be followed by S, B, M, E; may be followed by X; may be followed by two letters; followed by IP67.

ADONIS followed by H IQ, N IQ, IQW, RGBW, RGB, HYD, PRO, EXL, HE, HC, HEC, R, G, B; may be followed by HD; followed by 3 to 42; may be followed by W, TW; may be followed by 8, 9; may be followed by 18 to 65; may be followed by 1900 to 6000; followed by 77 to 4014; followed by one letter; may be followed by 10 to 90; may be followed by E, AS, CL, OL; followed by DC, MO, OO, OT; followed by S, B, M, E; may be followed by X; may be followed by two characters; followed by IP67.

KALYPSO may be followed by TC; followed by HYD, IQ W ATON, IQW ATON, IQ ATON, ATON IQ white, ECO, IQ W HYD, RGB, RGB 4S, IQ WHITE ATON, IQ WHITE HYDRA, HYDRA, NEX, RGBW, NEXUS, SOL, NEX IQW, NEX IQ W, NEX IQ WHITE, NEX IQWHITE, NEXUS IQ W, NEXUS IQW, NEXUS IQ WHITE, NEXUS IQWHITE, Linus, Linus+, LUMINARIS , LUM, LUMINARIS ECO, LUM ECO, IQW HYD, IQW NEX, IQ W NEX; may be followed by LD, HD; may be followed by 3 to 42; may be followed by P12 or P23; may be followed by L500, L1000, L1500, L2200; may be followed by R,G,B,A; may be followed by W; may be followed by 8, 9; may be followed by 20 to 50; may be followed by 0,077 to 4,014; may be followed by 77 to 4014; may be followed by 10 to 60; may be followed by D; followed by IP67.

VarioLED OCEANOS may be followed by TC; may be followed by 304/, 304/L, 316/, 316/L; may be followed by S,L or X; may be followed by IQ W ATON, IQ WHITE, IQWHITE, RGB, COLOR R, COLOR G, COLOR B, COLOR A, RGBW, IQW HYD, IQW NEX, PRO, EXL, IQ W NEX, IQ W HYD, NEX, SOL, HYD; may be followed by LD, HD; may be followed by 5 to 24; may be followed by W; may be followed by 8, 9; may be followed by 18 to 50; followed by 260 to 1200; followed by 10D, 30D or OP; followed by IP67 or IP68.

OCEANOS followed by HE, HC, HEC, ECO, RGB, IQW, R, G, B; may be followed by LD, HD; may be followed by 5 to 24; may be followed by W, TW; may be followed by 8, 9; may be followed by 18 to 65; may be followed by 1900 to 6000; followed by 260 to 1200; followed by 10D, 30D or OP; may be followed by DC, MO, OO, OT; may be followed by IFL, IFH; followed by IP67 or IP68.

XOOLINE followed by HYD, IQW, IQ W ATON, IQW ATON, IQ ATON, ATON IQ white, ECO, IQ W HYD, RGB, NEX, RGBW, NEXUS, SOL, NEX IQW, NEX IQ W, NEX IQ WHITE, NEX IQWHITE, NEXUS IQW, NEXUS IQ W, NEXUS IQWHITE, NEXUS IQ WHITE, Linus, Linus+, LUMINARIS , LUM, LUMINARIS ECO, LUM ECO, H IQ, N IQ, PRO, EXL; may be followed by LD, HD; may be followed by 3 to 42; may be followed by P12 or P23; may be followed by L500, L1000, L1500, L2200; may be followed by R,G,B,A; may be followed by W; may be followed by 8, 9; may be followed by 20 to 50; may be followed by 2240, 2250 or 2765; followed by 70 to 4014; may be followed by S or B; followed by 10D, 30D, 60D, 10, 30, 60, DR, NC, OR, CR, CL, OL, OH, DL, DH, AMB; may be followed by LS, FS, BS; may be followed by DC, MO, OO, OT; may be followed by -C002, -C004, MP, WMP, AMC, CL0, CL15, CL30, CL45, C00, C15, C30, C45, X, PCL; followed by IP67.

XOOLINE followed by PRO, EXL, HE, HC, HEC, SOL, H IQ, S IQ, IQW, RGB, ECO, R, G, B; may be followed by LD, HD; followed by 3 to 36; may be followed by W, TW; may be followed by 8, 9; may be followed by 18 to 99; may be followed by 1900 to 6000; followed by 77 to 4014; followed by one letter; followed by CR, DR, OR, CL, DL, OL, DH, OH; followed by LS, FS, BS; followed by DC, MO, OO, OT; followed by MP, C00, C15, C30, C45, PCL, AMC, WMP, X; followed by IP67.

XOOLUM may be followed by R; followed by HYD, IQ W ATON, IQ ATON, ATON IQ white, ECO, IQ W HYD, RGB, NEX, RGBW, SOL, ZEUS, ATON+, APOLLO, ATON2, ATON 2, ATON, DONAR, DUO, HERCULES, HYDRA, NEXUS, NEX IQW, NEX IQWHITE, NEXUS IQW, NEXUS IQWHITE, ATON IQ W, ATON PLUS, ATON COLOR, HYD COLOR, IQ WHITE, IQW A, ZEUS2, Linus, Linus+, LUMINARIS, LUM, LUMINARIS ECO, LUM ECO, IQW HYD, IQW NEX, PRO, EXL; may be followed by LD, HD; may be followed by 3 to 42; may be followed by P12 or P23; may be followed by L500, L1000, L1500, L2200; may be followed by R, G, B, A; may be followed by W; may be followed by 8, 9; may be followed by 20 to 50; followed by 73 to 4010; followed by S or B; may be followed by 25, 65, WW; may be followed by X, CL, OP, HO; followed by NA or A; followed by BS or FS; followed by IP67, IP68.

Xoolum followed by HYD, HE,HC, HEC, IQ W HYD, IQW, RGB, R, G, B; may be followed by HD, LD; followed by 3 to 36; may be followed by W, TW; may be followed by 8, 9; may be followed by 18 to 99; may be followed by 1900 to 6000; followed by 73 to 4010; followed by S, B; followed by 65, WW, OL; followed by BS, FS; followed by DC, MO, OO, OT; followed by S, P, TMC, SA, X; followed by IP67.

XOOLIGHT may be followed by HYD, IQ W ATON HD12, IQ W ATON HD24, RGB HD20, IQ W HYD, Linus, Linus+, IQW, PRO, EXL; may be followed by LD, HD; may be followed by 5 to 42; may be followed by W; may be followed by 8, 9; may be followed by 20 to 50; followed by 84 to 4021; followed by A, W; followed by BS, FS; followed by T, R; followed by IP67, IP68.

XOOLIGHT followed by HE, IQW, RGB, R, G, B; may be followed by HD; followed by 5 to 30; may be followed by 8, 9; may be followed by 18 to 65; may be followed by 1900 to 6000; followed by 84 to 4021; followed by one letter; followed by BS, FS; followed by T, R; followed by IP67.

XOOLIGHT followed by HE, HC, HEC, ECO, RGB, IQW, R, G, B; may be followed by LD, HD; followed by 5 to 30; may be followed by W, TW; may be followed by 8, 9; may be followed by 18 to 99; may be followed by 1900 to 6000; followed by 84 to 4021; followed by one letter; followed by BS, FS; may be followed by DC, MO, OO, OT; may be followed by S, P, R, X; followed by IP67.

VarioLED Flex followed by VENUS, PHOBOS, SKYLLA; followed by TC; followed by SV, TV, 3D; may be followed by W; may be followed by 8, 9; may be followed by 20 to 50; may be followed by /; followed by 74 to 5004; may be followed by IP67, IP68.

VENUS TC followed by TV, 3D; followed by 4 to 20; followed by W; followed by 8,9; followed by 18 to 65; followed by 74 to 3924; may be followed by two numbers; followed by OL,CL, E, AS; followed by DC, MO, OO, OT; may be followed by X; may be followed by three letters; followed by IP67.

LUNA may be followed by HYDRA, ECO, IQ White, IQ W, RGB; may be followed by ATON, HYD, IQW HYD, IQW NEX, PRO, EXL; followed by LD, HD, SLD; may be followed by 3 to 42; may be followed by W; may be followed by 8, 9; may be followed by 20 to 50; followed by 72,5 to 4010; may be followed by S, B, W; followed by NC, 10D, 30D, 60D, OR, DR, CR, OL, DL, CL, OH, DH, CH; followed by IP67.

LUNA followed by HE, IQW, RGB, R, G, B; may be followed by HD; followed by 5 to 42; may be followed by W; may be followed by 8, 9; may be followed by 18 to 65; may be followed by 1900 to 6000; followed by 73 to 4010; followed by S, B, W; followed by NC, OR, DR, CR, OL, DL, CL, OH, DH, CH; followed by DC, MO, OO, OT; may be followed by X; may be followed by two letters; followed by IP67.

LYRA may be followed by HYDRA, HYD, ATON AIR, IQ, ECO P12, ECO P23, RGB, SLD3, IQ W HYD, IQ W ATON, IQW HYD, IQW NEX, PRO, EXL; may be followed by LD, HD, L500, L1000, L1500, L2200; may be followed by 3 to 42; may be followed by W; may be followed by 8, 9; may be followed by 20 to 50; followed by 72,5 to 4010; may be followed by mm; followed by S, B; followed by OR, DR, CR, 10D, 30D, 60D; may be followed by V; followed by IP67.

LYRA followed by HE, IQW, RGB, R, G, B; may be followed by HD; followed by 5 to 42; may be followed by W; may be followed by 8, 9; may be followed by 18 to 65; may be followed by 1900 to 6000; followed by 73 to 4010; followed by S, B, W; followed by NC, OR, DR, CR, OL, DL, CL, OH, DH, CH; followed by DC, MO, OO, OT; may be followed by X; may be followed by two letters; followed by IP67.

VarioLED may be followed by Flex; followed by NIKE; may be followed by LD, HD, B, G, R; may be followed by 3 to 20; may be followed by W; may be followed by 8, 9; may be followed by 20 to 50; followed by 81 to 5048; followed by TV, SV, TVSB; followed by IP67, IP68.

XOOLUX NANO may be followed by IQ W; followed by LD, HD; followed by 3 to 40; may be followed by W; may be followed by 8, 9; may be followed by 20 to 50; followed by 71 to 4021; may be followed by 05 to 65; may be followed by OV; may be followed by B; followed by IP65, IP67.