




Offering lighting without hot spots at a 45-degree angle from a corner, this fixture excels at maximizing appeal of the products in displays, while maintaining a minimalist style.

### Features

- Offers lighting with a beam oriented at 45 degrees.
- Designed to give a uniform light with a round opal optic.
- Made of ALCOA 6063-T5 aluminum alloy increasing heat dissipation.
- Only available in North America.



Project name \_\_\_\_\_

Fixture type \_\_\_\_\_ Phase \_\_\_\_\_

Specifier \_\_\_\_\_ Date \_\_\_\_\_



**Linear weight:**  
0.12 lbs/ft (without optic)

**Cable Feed: End (E)**  
Max 4.7 W/ft


## Order Code

Family	LED Tape <sup>1</sup>	CRI	CCT	Optic	Cable / Connector <sup>4</sup>	Cable Position	Mounting <sup>3</sup>	Fixture length (mm)	Finish	Ingress
VarioLED 2200	-----	W_	---	---	---	---	---	-----	--	IP20
Corner	Nexus HD6-1.8 w/ft, 155 lm/ft	W8 85CRI	22 2200K <sup>2</sup>		FM Female & Male (4")	E End	SMC Surface Mount Clip	Refer to length chart on page 3	B - Black	IP20
	Nexus HD10-2.9 w/ft, 250 lm/ft	W9 95CRI	27 2700K	R5 Round Semi-Opal	M5 Male one side only (4")		AT Adhesive Tape		5 - Silver	
	Nexus HD15-4.7 w/ft, 400 lm/ft		30 3000K	RO Round Prime	OB Open Cable both sides (6')					
			35 3500K		OS Open Cable one side only (6')					
			40 4000K							
			50 5000K <sup>2</sup>							

<sup>1</sup> Delivered Lumens @3000K with Clear Optic. <sup>2</sup> Available only in 85CRI. <sup>3</sup> See Components spec sheet for details. <sup>4</sup> 2 x 22 AWG wires are supplied. See page 3 for more connectors.

## LED Tape Specifications

Color vector graphic




Color distortion graphic



- R<sub>r</sub> 92
- R<sub>g</sub> 101
- CRI 95
- R9 85

- 2200
- 2700
- 3000
- 3500
- 4000
- 5000 Kelvin

HD - High density / 8.93 mm LED pitch



L90/B10 > 60,000 h  
Wxxx/339

— Reference Illuminant — Test source @ 3000K

		HD6		HD10		HD15		Power (W/ft) <sup>A</sup>	HD6	HD10	HD15
		CCT	Lumen/ft	W/ft <sup>A</sup>	Lumen/ft	W/ft <sup>A</sup>	Lumen/ft				
Static White	● W822	2,200 K	140	1.8	240	2.9	390	4.7			
	● W927	2,700 K	150	1.8	260	2.9	410	4.7	24.6 / 7.5	16.4 / 5	16.4 / 5
	● W930	3,000 K	160	1.8	260	2.9	420	4.7	109	115	118
	● W935	3,500 K	160	1.8	270	2.9	430	4.7	95 / 75	95 / 75	95 / 75
	● W940	4,000 K	160	1.8	270	2.9	440	4.7	95 / 100	95 / 100	95 / 100
	● W850	5,000 K	190	1.8	340	2.9	550	4.7	122°F / 50°C	122°F / 50°C	113°F / 45°C
	●										


<sup>A</sup> Lumen values represent bare LED tape. Refer to page 2 to calculate delivered fixture lumens by using the light efficiency percentages.

<sup>B</sup> The given data are typical values. Due to tolerances of the production process and the electrical components, values for light output and electrical power can vary up to 10%.

## Technical Details

### ROUND SEMI-OPAL

85% light transmittance




Slight visible dotting  
CCT decrease 130 K

This lens reduces glare and softens light cut-off while maintaining high brightness.

### ROUND PRIME

50% light transmittance



Minimal Visible Dotting  
CCT decrease 215 K


This light opal lens reduces glare and softens light cut-off while maintaining the high output levels and greatly diffusing the LED diode image on the surface.

## Mounting Dimensions [mm] in




AT  
Adhesive Tape

### ROUND LENS



SMC  
Surface Mount Clip



### ROUND LENS



## LENGTH CHART

Fixture length		HD6 1.8 Watts/Ft		HD10 2.9 Watts/Ft		HD15 4.7 Watts/Ft	
inches	mm	Watts/fixture	Lumens/fixture @3000K	Watts/fixture	Lumens/fixture @3000K	Watts/fixture	Lumens/fixture @3000K
3.2	83	0.5	42	0.8	68	1.2	108
5.7	145	0.9	74	1.4	119	2.2	190
8.2	208	1.2	105	2.0	170	3.1	272
10.6	270	1.6	137	2.7	221	4.1	354
13.1	333	2.0	169	3.3	273	5.0	436
15.6	395	2.3	201	3.9	324	6.0	518
18.0	458	2.7	233	4.5	375	6.9	600
20.5	520	3.1	264	5.1	426	7.8	682
22.9	583	3.4	296	5.7	478	8.8	764
25.4	645	3.8	328	6.3	529	9.7	846
27.9	708	4.2	360	7.0	580	10.7	928
30.3	770	4.5	391	7.6	631	11.6	1010
32.8	833	4.9	423	8.2	683	12.6	1092
35.2	895	5.3	455	8.8	734	13.5	1174
37.7	958	5.7	487	9.4	785	14.4	1256
40.2	1020	6.0	519	10.0	836	15.4	1338
42.6	1083	6.4	550	10.7	888	16.3	1420
45.1	1145	6.8	582	11.3	939	17.3	1502
47.5	1208	7.1	614	11.9	990	18.2	1584
50.0	1270	7.5	646	12.5	1041	19.2	1666
52.5	1333	7.9	677	13.1	1093	20.1	1748
54.9	1395	8.2	709	13.7	1144	21.0	1830
57.4	1458	8.6	741	14.3	1195	22.0	1912
59.8	1520	9.0	773	15.0	1246	22.9	1994
62.3	1583	9.3	805	15.6	1298	23.9	2076
64.8	1645	9.7	836	16.2	1349	24.8	2158
67.2	1708	10.1	868	16.8	1400	25.8	2240
69.7	1770	10.5	900	17.4	1451	26.7	2322
72.1	1833	10.8	932	18.0	1503	27.6	2404
74.6	1895	11.2	963	18.6	1554	28.6	2486
77.1	1958	11.6	995	19.3	1605	29.5	2568


## Connectors

Item	Description	Model	Dimensions	Order Code
	Use to connect the driver to the beginning of the LED tape run or to the next LED tape section. Female mini connector on one side and open end cable on the other side.	Static White	2 x 22 Awg, 6.5 ft	15000147
	Use to extend the distance between connection points. Female mini connector on one side and male mini connector on the other side.	Static White Static White	2 x 22 Awg, 3.2 ft 2 x 22 Awg, 6.5 ft	15000148 15000149

## Compatible Drivers

Item	Specifications	Downloads
<b>LED LINEAR™</b> Non-Dimmable Drivers 	<ul style="list-style-type: none"> <li>• UL 8750 Listed Enclosure - With Built-In Junction Boxes</li> <li>• Universal Input Voltage 120V - 277V</li> <li>• IP65 - For Both Indoor and Outdoor Use</li> <li>• No Minimum Load Requirement</li> <li>• 24V Constant Voltage Output, Class 2</li> <li>• Available in three wattages 30W, 60W and 96W</li> <li>• Max. Dimensions: 12-1/8" x 2-3/8" x 1-3/8"</li> </ul>	<a href="#">30 W SPEC SHEET</a> <a href="#">60 W SPEC SHEET</a> <a href="#">96 W SPEC SHEET</a> <a href="#">INSTALLATION INSTRUCTIONS</a>
<b>LED LINEAR™</b> 0-10V Dimmable Drivers 	<ul style="list-style-type: none"> <li>• UL 8750 Listed Enclosure - With Built-In Junction Boxes</li> <li>• 0-10V Dimmable - Flicker Free Down to 1%</li> <li>• Universal Input Voltage 120V - 277V</li> <li>• IP65 - For Both Indoor and Outdoor Use</li> <li>• 24V Constant Voltage Output, Class 2, Class P</li> <li>• Available in three wattages 30W, 60W and 96W</li> <li>• Max. Dimensions: 12-1/8" x 2-3/8" x 1-3/8"</li> </ul>	<a href="#">30 W SPEC SHEET</a> <a href="#">60 W SPEC SHEET</a> <a href="#">96 W SPEC SHEET</a> <a href="#">INSTALLATION INSTRUCTIONS</a>
<b>LED LINEAR™</b> ELV/Triac Dimmable Drivers 	<ul style="list-style-type: none"> <li>• UL 8750 Listed Class 2 Enclosure</li> <li>• 24V constant voltage output</li> <li>• Compact size yet high efficiency and performance in dry and damp environments (IP67)</li> <li>• Multiple Inputs: 120V or 277V</li> <li>• Fully dimmable: ELV Dimmers - Reverse or Adaptive Phase Control, Trailing Edge</li> <li>• Available in two wattages 48W and 96W</li> <li>• Multiple Circuits are available up to 4 units (up to 384W)</li> </ul>	<a href="#">48 W SPEC SHEET</a> <a href="#">96 W SPEC SHEET</a> <a href="#">INSTALLATION INSTRUCTIONS</a>
 PWM Dimmable Drivers 	<ul style="list-style-type: none"> <li>• Universal AC input / Full range (up to 305VAC)</li> <li>• Constant voltage PWM style output</li> <li>• Built-in 3 in 1 dimming function (0-10Vdc or PWM signal or resistance)</li> <li>• Dimming range : 0-100%</li> <li>• Class 2 power unit</li> <li>• Suitable for dry / damp / wet locations</li> <li>• UL Recognized component, 5 years warranty</li> </ul>	<a href="#">40 W SPEC SHEET</a> <a href="#">60 W SPEC SHEET</a> <a href="#">90 W SPEC SHEET</a> <a href="#">INSTALLATION INSTRUCTIONS</a>
<b>OLUTRON</b> Dimmable Drivers 	<ul style="list-style-type: none"> <li>• UL Listed Enclosure</li> <li>• Dimming Range: 100% to 1% and 0.1% (Premiere)</li> <li>• LED lighting turns on to any dimmed level without flashing to full brightness</li> <li>• Operating Voltage: 120V~ to 277V~ at 50/60 Hz</li> <li>• Rated lifetime of 50,000 hours at 40°C (104°F) ambient temperature and maximum loading</li> <li>• For rated warranty, ambient temperature not to exceed 40°C (104°F)</li> <li>• Open-circuit protected output</li> </ul>	<a href="#">HI-LUME SPEC SHEET</a> <a href="#">HI-LUME PREMIERE SPEC SHEET</a> <a href="#">INSTALLATION INSTRUCTIONS</a>
<b>eldoLED</b> DALI/DMX Dimmable Drivers 	<ul style="list-style-type: none"> <li>• Available in linear or rectangular format</li> <li>• 100W, DMX/DALI interface for Static White, Tunable White and RGB/W Applications</li> <li>• 4 control channels</li> <li>• 24V constant voltage, 4 x 24V outputs</li> <li>• Metal or plastic case options</li> </ul>	<a href="#">100 W SPEC SHEET</a> <a href="#">INSTALLATION INSTRUCTIONS</a>

## Controllers

Item	Specifications	Downloads
<b>eldoLED</b> Controllers 	<b>180/D</b> DMX Controller for RGB/W and Tunable White Applications	<a href="#">180/D SPEC SHEET</a>
	<b>210/D</b> Dali Controller for Static White Applications	<a href="#">210/D SPEC SHEET</a>
	<b>211/D-LG</b> 0-10V Logarithmic Dimming Controller	<a href="#">211/D-LG SPEC SHEET</a>
	<b>211/D-LN</b> 0-10V Linear Dimming Controller	<a href="#">211/D-LN SPEC SHEET</a>
	<b>212/D</b> DMX Controller for Static White and Static Color Applications	<a href="#">212/D SPEC SHEET</a>
	<b>DimWheel</b> DMX Wall Controller for RGB/W and Tunable White Applications	<a href="#">DIM WHEEL SPEC SHEET</a>

Click for more information

VOLTAGE DROP CALCULATOR

INSTALLATION

LED LINEAR TECHNOLOGY