

Contour 5560 Aluminum Profile

LED LINEAR™



The 5560 profile allows integrating linear LED lighting on curved or uneven surfaces. Its low profile of less than 1/32" (0.75mm), allows for effortless bending and installation using plain mounting tape.

Features

- Delivered in standard 6.5 ft (2m) length.
- Thin, lightweight and flexible, can be easily bent both inside and outside over curved or uneven surfaces.
- Can be installed using adhesive mounting tape.
- Designed to meet North American woodworking standards.
- Made of ALCOA 6063-T5 aluminum alloy increasing heat dissipation.
- Its use increases the lifetime of your LED strip.
- Max bending radius is 4 inches.
- Only available in North America.

Project name

Fixture type

Specifier

Phase

Date

ALCOA
6063-T5
ANODIZED
ALUMINUM

ALU

Linear weight:

0.04 lbs/ft (without optic)

Cable Feed: Behind (B)

Max 4.7 W/ft


Component Order Code

Family	Profile	Optic	Mounting
Contour	5560	5570	1033

Technical Details

OPAL

50% light efficiency



Visible dotting

CCT decrease 215 K


This basic lens protects your tape and maximizes light output.

Mounting Dimensions [mm] in




Adhesive Tape

WITHOUT LENS



WITH LENS



Max Bending Radius: 4 inches

LED FLEX TAPE COMPATIBILITY CHART

✓ Compatible

☑ Dot free

LED Tape Family	LED Tape Type	Models ¹	LED Tape Step Length	Contour 5560 Compatibility
LUMINARIS	Static White	Luminaris LD05 (1.7W/ft, 152lm/ft)	2.76"/70mm	✓
		Luminaris LD10 (2.6W/ft, 311lm/ft)	2.76"/70mm	✓
		Luminaris LD15 (4.7W/ft, 463lm/ft)	2.76"/70mm	✓
		Luminaris LD22 (6.3W/ft, 659lm/ft)	2.76"/70mm	
		Luminaris HD05 (1.6W/ft, 201lm/ft)	2.76"/70mm	✓
		Luminaris HD10 (2.6W/ft, 320lm/ft)	2.76"/70mm	✓
		Luminaris HD15 (4.7W/ft, 552lm/ft)	2.76"/70mm	✓
		Luminaris HD22 (6.3W/ft, 716lm/ft)	2.76"/70mm	
HYDRA	Static White	Hydra PRO 07 (1.9W/ft, 185lm/ft)	2.46"/62.5mm	✓
		Hydra PRO 13 (3.9W/ft, 430lm/ft)	2.46"/62.5mm	✓
		Hydra PRO 18 (5.6W/ft, 600lm/ft)	2.46"/62.5mm	
		Hydra PRO 24 (7.4W/ft, 750lm/ft)	2.46"/62.5mm	
		Hydra PRO 35 (10.7W/ft, 1100lm/ft)	2.46"/62.5mm	
	Tunable White	Hydra Tunable LD25 (7.6W/ft, 503lm/ft)	4.92"/125mm	
		Hydra Tunable HD12 (3.6W/ft, 213lm/ft)	2.46"/62.5mm	✓
		Hydra Tunable HD24 (7.2W/ft, 472lm/ft)	2.46"/62.5mm	
	RGB	Hydra RGB LD15 (4.6W/ft, 127lm/ft)	4.92"/125mm	✓
		Hydra RGB HD10 (3.4W/ft, 102lm/ft)	2.46"/62.5mm	✓
Hydra RGB HD20 (6.7W/ft, 191lm/ft)		2.46"/62.5mm		
STATIC COLOR	Static Color	Static Color HD (3.1W/ft, 300lm/ft)	2.76"/70mm	✓

1) Lumen values reflect measurements of LED tape at 3000K. Tunable White, RGB and Static Color represent the highest possible lumen output.

Click for more information

LED FLEX TAPE

PROFILES & OPTICS

DRIVERS & CONTROLLERS